


Solenoid valve	Inlet/outlet pipe connections	External connection	Cut-off automatic valve
	M12X1	G~1/2	APUS000
10)/	M14X1	G"1/2	APUS001
12V	1/4"-18 NPT	G"1/2	APUS002
	1/4" GAS	G″1/2	APUS003
	M12X1	G"1/2	APUS010
201	M14X1	G"1/2	APUS011
24V	1/4"-18 NPT	G″1/2	APUS012
	1/4" GAS	G"1/2	APUS013

- In line cut-off automatic valve
 Low absorption solenoid valve
 Universal thread connections available to match every application
 CNG inlet filtering system
 Max working pressure: 260 bar
 Working temperature: -40 + 120°C

ECE R110 ISO 15500 CERTIFIED








Solenoid valve	Inlet pipe connection	Outlet pipe connection	External connection	Cut-off automatic valve
12V	M12X1	G"1/2 female	G"1/2	APUS1

ECE R110 ISO 15500 **CERTIFIED**

- In line cut-on automatic valve
 Low absorption solenoid valve
 Universal thread connections available to match every application
 CNG inlet filtering system
 Max working pressure: 260 bar
 Working temperature: -40 + 120°C







ECE R110 ISO 15500 **CERTIFIED**

- Cut-off valve for reducer
 Low absorption solenoid valve
 Different threads for connection on reducers available

